



TRUSTED PERFORMERS SERIES



JAPANESE STANDARD

SMALL APPLIANCE BATTERY



POWER MASTER

Features	Model: WB440	Model: WB460	Model: WB6450B	Model: WB6450C	Model: WB680
Nominal Voltage	4 V	4 V	6 V	6 V	6 V
Nominal Capacity	4.0 AH @ 20 Hour	6 AH @ 20 Hour	4.25 AH @ 20 Hour	4.25 AH @ 20 Hour	8 AH @ 20 Hour
Weight	440 ± 20 grams	645 ± 20grams	725 ± 20 grams	725 ± 20 grams	1130 ± 20 grams
Maximum Charging Current	1.25 A	1.8 A	1.35 A	1.35 A	2.1 A
Float Charging Voltage	4.6 ~ 4.8 VDC	4.6 ~ 4.8 VDC	7.2 ~ 7.4 VDC	7.2 ~ 7.4 VDC	7.2 ~ 7.4 VDC
Product Dimension (LxWxH)	(47x47x100) mm	(70x47x100) mm	(70x46.5x104) mm	(70x46.5x100) mm	(151x35.5x94.5) mm
Terminal	F1	F1	Sunca	F1	F1

Features	Model: WB1245	Model: WB1282	Model: WB1290	Model: WB1212
Nominal Voltage	12 V	12 V	12 V	12 V
Nominal Capacity	4.5 AH @ 20 Hour	8.2 AH @ 20 Hour	9 AH @ 20 Hour	12 AH @ 20 Hour
Weight	1450 ± 20 grams	2150 ± 20 grams	2500 ± 25 grams	3345 ± 50 grams
Maximum Charging Current	1.35 A	2.46 A	2.70 A	3.6 A
Float Charging Voltage	14.4 ~ 14.8 VDC	14.4 ~ 14.8 VDC	14.4 ~ 14.8 VDC	13.8 ~ 14.4 VDC
Product Dimension (LxWxH)	(90x70.5x100.5) mm	(151x65x94) mm	(151x65x94) mm	(150.6x98x100) mm
Terminal	F1	F2	F2	F2

SKYVOLTZ

Features	Model: 440	Model: 6450B	Model: 6450C	Model: 670	Model: 1245
Nominal Voltage	4 V	6 V	6 V	6 V	12 V
Nominal Capacity	4.0 AH @ 20 Hour	4.25 AH @ 20 Hour	4.25 AH @ 20 Hour	7 AH @ 20 Hour	4.5 AH @ 20 Hour
Weight	418 ± 25 grams	655 ± 25 grams	655 ± 25 grams	1054 ± 25 grams	1317 ± 25 grams
Maximum Charging Current	1.25 A	1.35 A	1.35 A	2.1 A	1.35 A
Float Charging Voltage	4.6 ~ 4.8 VDC	7.2 ~ 7.4 VDC	7.2 ~ 7.4 VDC	7.2 ~ 7.4 VDC	14.4 ~ 14.8 VDC
Product Dimension (LxWxH)	(47x47x100) mm	(70x46.5x104) mm	(70x46.5x100) mm	(151x35.5x94.5) mm	(90x70.5x100.5) mm
Terminal	F1	Sunca	F1	F1	F1

Features	Model: 1275	Model: 1290
Nominal Voltage	12 V	12 V
Nominal Capacity	7.5 AH @ 20 Hour	9 AH @ 20 Hour
Weight	2050 ± 25 grams	2170 ± 25 grams
Maximum Charging Current	2.25 A	2.70 A
Float Charging Voltage	14.4 ~ 14.8 VDC	14.4 ~ 14.8 VDC
Product Dimension (LxWxH)	(151x65x94) mm	(151x65x94) mm
Terminal	F2	F2



MOTORCYCLE BATTERY



HYPERVOLTZ

Features	Model: 12N2.5-BS	Model: YTX4L-BS	Model: YTX5L-BS	Model: 12N5-BS	Model: 12N6.5-BS
Nominal Voltage	12 V	12 V	12 V	12 V	12 V
Nominal Capacity	2.5 AH @ 20 Hour	4 AH @ 20 Hour	5 AH @ 20 Hour	5 AH @ 20 Hour	6.5 AH @ 20 Hour
Weight	1.05 ± 0.05 kg	1.32 ± 0.05 kg	1.80 ± 0.05 kg	1.82 ± 0.05 kg	2.01 ± 0.05 kg
Maximum Charging Current	0.25 A	0.4 A	0.5 A	0.5 A	0.65 A
Float Charging Voltage	14.3~14.8 VDC	14.3~14.8 VDC	14.3~14.8 VDC	14.3~14.8 VDC	14.3~14.8 VDC
Product Dimension (LxWxH)	(79.5x76.6x103) mm	(113.8x68.6x86) mm	(113.8x68.6x108.5) mm	(118.5x60.6x126.5) mm	(139x67x103.5) mm
Terminal	Cable Type	Lead Alloy	Lead Alloy	Lead Alloy	Lead Alloy

Features	Model: 12N7-BS	Model: 12N9-BS
Nominal Voltage	12 V	12 V
Nominal Capacity	7 AH @ 20 Hour	9 AH @ 20 Hour
Weight	2.30 ± 0.05 kg	2.88 ± 0.05 kg
Maximum Charging Current	0.70 A	0.9 A
Float Charging Voltage	14.3~14.8 VDC	14.3~14.8 VDC
Product Dimension (LxWxH)	(146x59.5x127) mm	(137.5x77.5x134) mm
Terminal	Lead Alloy	Lead Alloy

ROAD RIDER

Features	Model: 12N2.5-BS	Model: YTX4L-BS	Model: YTX5L-BS	Model: 12N5-BS	Model: 12N6.5-BS
Nominal Voltage	12 V	12 V	12 V	12 V	12 V
Nominal Capacity	2.5 AH @ 20 Hour	4 AH @ 20 Hour	5 AH @ 20 Hour	5 AH @ 20 Hour	6.5 AH @ 20 Hour
Weight	1.05 ± 0.05 kg	1.37 ± 0.05 kg	1.90 ± 0.05 kg	1.95 ± 0.05 kg	2.01 ± 0.05 kg
Maximum Charging Current	0.25 A	0.4 A	0.5 A	0.5 A	0.65 A
Float Charging Voltage	14.3~14.8 VDC	14.3~14.8 VDC	14.3~14.8 VDC	14.3~14.8 VDC	14.3~14.8 VDC
Product Dimension (LxWxH)	(79.5x76.6x103) mm	(113.8x68.6x86) mm	(113.8x68.6x108.5) mm	(118.5x60.6x126.5) mm	(139x67x103.5) mm
Terminal	Cable Type	Lead Alloy	Lead Alloy	Lead Alloy	Lead Alloy

Features	Model: YTX7L-BS	Model: 12N7-BS	Model: 12N9-BS
Nominal Voltage	12 V	12 V	12 V
Nominal Capacity	7 AH @ 20 Hour	7 AH @ 20 Hour	9 AH @ 20 Hour
Weight	2.32 ± 0.05 kg	2.46 ± 0.05 kg	2.88 ± 0.05 kg
Maximum Charging Current	0.7 A	0.7 A	0.9 A
Float Charging Voltage	14.3 ~ 14.8 VDC	14.3~14.8 VDC	14.3~14.8 VDC
Product Dimension (LxWxH)	(113.8x68.6x130.5) mm	(146x59.5x127) mm	(137.5x77.5x134) mm
Terminal	Lead Alloy	Lead Alloy	Lead Alloy



ONLINE UPS BATTERY



POWER MASTER (Online UPS Battery)

Features	Model: WBU1218	Model: WBU1226	Model: WBU1240	Model: WBU1265	Model: WBU1280
Nominal Voltage	12 V	12 V	12 V	12 V	12 V
Nominal Capacity	18 AH @ 20 Hour	26 AH @ 20 Hour	40 AH @ 20 Hour	65 AH @ 10 Hour	80 AH @ 10 Hour
Weight	5.30 ± 0.075 kg	8.48 ± 0.085 kg	12.12 ± 0.15 kg	19.92 ± 0.10 kg	23.81 ± 0.10 kg
Maximum Charging Current	5.4 A	7.8 A	12 A	19.5 A	24 A
Float Charging Voltage	14.3 ~ 14.8 VDC	14.3 ~ 14.8 VDC	14.3 ~ 14.8 V	14.3 ~ 14.8 V	14.3 ~ 14.8 VDC
Product Dimension (LxWxH)	(181x77.5x165) mm	(166x175x123.5) mm	(196.5x165x169) mm	(348x167x178) mm	(260x168x214) mm
Terminal	Silver-coated Copper	Silver-coated Copper	Silver-coated Copper	Silver-coated Copper	Silver-coated Copper

Features	Model: WBU12100	Model: WBU12120	Model: WBU12150	Model: WBU12200
Nominal Voltage	12 V	12 V	12 V	12 V
Nominal Capacity	100 AH @ 10 Hour	120 AH @ 10 Hour	150 AH @ 10 Hour	200 AH @ 10 Hour
Weight	29.06 ± 0.10 kg	34.32 ± 0.10 kg	41.41 ± 0.10 kg	59.05 ± 0.10 kg
Maximum Charging Current	30 A	36 A	45 A	60 A
Float Charging Voltage	14.3 ~ 14.8 VDC	14.3 ~ 14.8 VDC	14.3 ~ 14.8 VDC	14.3 ~ 14.8 VDC
Product Dimension (LxWxH)	(330x173x220) mm	(408x177x225) mm	(483x170x238.5) mm	(522x240x224) mm
Terminal	Silver-coated Copper	Silver-coated Copper	Silver-coated Copper	Silver Coated Copper

Walton Group

Headquarters and R&I Center
Chandra, Kaliakoir, Gazipur, Bangladesh
Email: global@waltonplc.com

Corporate Office (Bangladesh)
Plot # 1088, Block # 1, Road # Sabrina Sobhan 5th Avenue
Bashundhara R/A, Vatara, Dhaka-1229, Bangladesh
Tel: +860 9606-555 555, Fax: +880 9606-555 550
Email: global@waltonplc.com

Corporate Office (Global)
12225 Greenville Avenue, Suite # 880, Dallas
Texas 75243, USA, Email: global@waltonplc.com

R&I Office (Global)
361 Dakkum Business Center, 3rd Floor
7-3 Gwanggyo Jungang-ro, 248 beon-gil
Yeongtong-gu, Suwon-si, Gyeonggi-do
Republic of Korea



SCAN FOR E-CATALOGUE

Please visit waltonbd.com

- More Durable
- Extended Life Cycle
- Maintenance Free